



新料号 1041A0-***-1G1



Pin#	A	B	C
4	3	5.1	7.5
5	4	6.1	8.5
6	5	7.1	9.5
7	6	8.1	10.5
8	7	9.1	11.5
9	8	10.1	12.5
10	9	11.1	13.5
11	10	12.1	14.5
12	11	13.1	15.5
13	12	14.1	16.5
14	13	15.1	17.5
15	14	16.1	18.5
16	15	17.1	19.5
17	16	18.1	20.5
18	17	19.1	21.5
19	18	20.1	22.5
20	19	21.1	23.5
21	20	22.1	24.5
22	21	23.1	25.5
23	22	24.1	26.5
24	23	25.1	27.5
25	24	26.1	28.5
26	25	27.1	29.5
27	26	28.1	30.5
28	27	29.1	31.5
29	30	30.1	32.5
30	29	31.1	33.5
31	30	32.1	34.5
32	31	33.1	35.5
33	32	34.1	36.5
34	33	35.1	37.5
35	34	36.1	38.5

使用类别 (EXTEND) USE

1. 0单面接弯针

尺寸公差

DIMENSION	±0.30
	±0.20
	±0.10
	±0.05

角度公差

ANGLES	±3°
	±2°
	±1°

原材料 (MATERIAL)

单位 (UNIT)	mm
数量 (QTY)	
表面处理 (FINISHED)	

核准 (APPD)

审核 (CID)	尹彩艳
绘图 (DRW)	尹彩艳

深圳市三佐部品电子有限公司

料号 (P/N):

1041A0-***-1G1

页数 (SHEET) 1/1 比例 (SCALE) 1:1

版次 (REV) X1

变更编号 (ECN NO)

说明 (DESCRIPTION)

初版发行

日期 (DATE)

核准 (APPD)