



- Notes:
- 1 Dimensions shall be interpreted per ASME Y14.5M.
 - 2 Mechanical performance(See the table 1)
<2.1>The force is the average of forces obtained when plunger goes downwards and upwards.
 - <2.2>Warning: Working height are not permitted to be less than Min working height.
 - 3 Electrical performance
Resistance: 30mOhm Max.Current rating: 2.0A
 - 4 RoHS compliant.

Max working height	8.80mm	60 ⁺⁶⁰ / ₋₂₀ fg
Min working height	8.30mm	80 ⁺⁶⁰ / ₋₂₀ fg
Durability	10000cycle	

Item	Part name	Qty/Ed ¹	Material	Finish
1	Body	1	Leaded Brass	Au 0.1um plating Ni 1.4um
2	Plunger	1	Leaded Brass	Au 0.4um plating Ni 1.4um
3	Spring	1	Stainless steel wire	
4				
5				

Rev.	Change	Date.
B1	Update	2012/12/19
B	change spring	2008/04/21
A	NEW	2008/04/01
	Revision record.	

Top-Link Electronics Ltd.		Type	Customer drawing	Unit	mm	Weight
TOLERANCES UNLESS OTHER SPECIFIED		DWN:	Coi wanlu	APVD:		
0.0	±0.15	CHK:		REL:		
0.00	±0.10	Name	POGO PIN			
0.000	±0.05	Scale	1:1	Size	A4	DWG No.
ANGLE: ±1°		Scale	1:1	Size	A4	DWG No.
SURF. TEXTURE: REMOVE SHARP EDGES R0.05 MAX.DO NOT SCALE PRINT.		Scale	1:1	Size	A4	DWG No.

三佐株式会社

101164-1
PART NUMBER

Page 1/1
Rev. B1