



Notes:

- 1)Plunger & Body : CuZn36 Pb3, HO2 (C36000)  
or CuZn39 PB3 or CuZn38 PB2.
- 2)Spring : Stainless steel wire
- 2 Plating
- 1)Body: Min 0.1um Gold plating over min. 1.4um Nickel plating
- 2)Plunger: Min 0.4um Gold plating over min. 2.5um Nickel plating
- 3 Mechanical
- 1)Total stroke : 1.5mm
- 2)Durability: 10,000 cycle min.
- 4 Electrical
- 1)Contact resistance: 20mOhm Max.
- 2)Operating voltage: 8VDC

LDC	-
DIST	-

LTR	REVISION RECORD	APVD	DATE

DIMENSIONS IN MM  
TOLERANCES UNLESS  
OTHER SPECIFIED

0 = ±  
0.0 = ±0.10  
0.00 = ±  
0.000 = ±

ANGLE: ±1°

SURF TEXTURE: 3.2/

REMOVE BURRS, BREAK  
SHARP EDGES R0.05 MAX  
DD NOT SCALE PRINT

MATL	HT TR	FIN
DWN Benny	APVD Lansing	REL
CHK Andy	pogo pin (PG-1.5-5.0-RA-1)	
SCALE 1:1	A4	DWG NO. C-101004
SHEET 1 OF 1		REV A

三佐株式会社

101004-1
Part Number

USED DN

4 3 2 1