



PART NO.	A	B	C	D
DZWF540HBAA0	1.85	3.8	5.4	4.6
DZWF600HBAA0	1.85	4.4	6.0	5.2
DZWF700HBAA0	1.85	5.4	7.0	6.2
DZWF800HBAA0	1.85	6.4	8.0	7.2

性能:

- 额定电流: 2.0A
- 额定电压: 12V
- 耐压: 500V
- 接触电阻: 30mΩ
- 绝缘电阻: 500MΩ
- 工作温度: -40℃~+85℃
- 塑件(材质): LCP
- 接触点(材质): 磷铜, 镀金

版次REV.	更新内容REVISIONNOTE	日期DATE	公差公差 TOLERANCE		三佐部品【中国】股份有限公司			
			X. ±0.35	X.' ±4'			品名ARTICLE: 电池连接器	
			XX ±0.25	X.X' ±3'				
绘制DRAWN	彭育春		X.XX ±0.15	X.XX ±0.25'	图物MODEL: DZWF-□□□-HBAA0			
设计DES'D	付坚强		X.XXX ±0.05	X.XXX ±0.1			A4	
审核CHK'D	叶泽奇		视图方法 PROJECTION		图物MODEL: DZWF-□□□-HBAA0			
批准APP'VD	张志敬						A4	
			比例SCALE: 3:1		单位UNIT: mm			
					页码SHEET: 共1页 第1页			