


RECOMMENDED PCB LAYOUT

TOL: (±0.05)



性能:

- 额定电流: 3A
- 额定电压: 30V
- 耐电压: 500V
- 接触电阻: 30mΩ
- 绝缘电阻: 500MΩ
- 工作温度: -55℃~+125℃
- 塑件(材质): PA9T
- 接触点(材质): 磷铜, 镀金5U

Pin数	PART NO.	DIM A	DIM B
2P	DZUK400CADA0	7.7	5.11
3P	DZUK400CBDA0	11.7	9.11
4P	DZUK400CCDA0	15.7	13.11
5P	DZUK400CDDA0	19.7	17.11
6P	DZUK400CEDA0	23.7	21.11

原形REV.	日期DATE	规格书 TOLERANCE		三任部品【中国】股份有限公司
201705022	2017.05.05	X. ±0.35	X1: ±0.1	
		X. ±0.25	X1: ±0.7	
		X.XX ±0.15	X.XX ±0.2	
绘制DRAWN	KevinMao	X.XXX ±0.05	X.XXX ±0.1	零件图: 电池连接器
校核DES'D	KevinMao	投影方式 PROJECTION		
审核CHK'D	EricPeng			MODEL: DZUK400C-□-DA0 A4
批准APP'VD				比例SCALE: